

Ø 24.00 -27.63 9.88 Ø 17.50 – 10.50 -22.38

3. CLASS: 300#

4. END CONNECTION: FLANGED

5. WEIGHT: 576 LBS

6. Cv: 17350

7. PRESSURE RANGE: 720 PSI

8. TEMPERATURE RANGE: UP TO 1000°F

9. MOUNTING DIMENSIONS: CONSULT FACTORY



6910 West Ridge Road Fairview, PA 16415, USA Phone: (814) 474-2666 Web: www.jareckivalves.net Email: sales@jareckivalves.net

THE INFORMATION CONTAINED HEREIN SHALL BE CONSIDERED THE SOLE PROPERTY OF JARECKI VALVES. THE RECIPIENT THEREIF AGREES NOT TO DISCLOSE SAID INFORMATION FOR THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF T FOR ANY PURPOSE EXCEPT AS SPECIFIED BY JARECKI VALVES, BY WRITTEN PERMISSION.

Tolerances (Inch) $.xx = \pm .01$ $.xxx = \pm .005$ $x^{\circ} = \pm 1^{\circ}$ or As Note			UNIT
		10-SVF-03B/0 300# ANSI	iO inch
			SIZE
	r	SV SERIES	
SCALE			s A

**COMPONENT** 

**BALL VALVES** 

## ORDERING INFORMATION

	PORT SIZE	SEAT	SEAT MATERIAL	BALL	BALL COATING	BODY	- CLASS	END CONNECTION	OPTIONS
l ev	F FULL R REDUCED	0 NONMETAL 1 O SEAT 2 G SEAT 4 P SEAT 5 P SEAT >750F	B BORONIZING C COLMONOY G GRAPHITE M TANTALUM CHROME OXIDE P PEEK R CHROME CARBIDE S STELLITE T TFE U UHMWPE	A 316SST F HASTELLOY G INCOLOY H ALLOY 20 I MONEL X 2205 SST	B BORONIZING C CHROME E ENP M TANTALUM CHROME OXIDE L COLMONOY R CHROME CARBIDE S STELLITE T TFE W TUNGSTEN CARBIDE	A CF8M B WCB H Alloy 20 X 2205 SST	01 150# 03 300#	B FLANGED D BUTT WELD	V90 90DEG V V60 60DEG V V30 30DEG V V15 15DEG V SL12 SLOT.125 SL063 SLOT.063

## Example:

2"	SV SERIES	FULL PORT	SPRING LOADED UNIDIRECTIONAL SEATS	STELLITE SEATS	316SS	CHROME	CF8M	150#	FLANGED RF
2	-SV	F	4	S	Α	С	Α	-01	В

Ordering Information:
When placing an order or requesting a quotation, please provide as many details on the application as possible such as media type, temperature, pressure, pipe size, etc.

	_				
n/	\п				
10	V				
	ARECKI				
VALVES					
L					

6910 West Ridge Road Fairview, PA 16415, USA Phone: (814) 474-2666 Web: www.jareckivalves.net Email: sales@jareckivalves.net

THE INFORMATION CONTAINED HEREIN SHALL BE CONSIDERED THE SOLE PROPERTY OF JARECKI VALVES. THE RECIPIENT THEREIF AGREES NOT TO DISCLOSE SAID INFORMATION FOR ANY PURPOSE EXCEPT AS SPECIFIED BY JARECKI VALVES, BY WRITTEN PERMISSION.

Tolerance .xx = .xxx = x° = or As	± .01 ± .005 ± 1°	
SCALE	NTS	

COMPONENT	BALL VALVES
	UNIT
10-SVF-03B/G 300# ANSI	GO INCH
SV SERIES	SIZE
2-Piece Ball Valve	es A